co-ax® Valve Specification Sheet

müller coax group

Company: _____ **Date:** _____

Contact: _____

Address: _____

City/State/Zip: _____

Phone: _____

E-Mail: _____

Reference: _____

Scan to learn more...

☐ **OEM**
☐ **Reseller**
☐ **End User**

Function:
☐ Normally Closed
☐ Normally Open

Design:
☐ 2/2 Way
☐ 3/2 Way
☐ Manifold

Actuation
☐ Direct (solenoid)
☐ Externally (air)
☐ Externally (other)

Voltage:
☐ 24 V DC
☐ 110 V AC
☐ Other

Approvals:
☐ ATEX
☐ CSA/UL
☐ IECEx
☐ Zone I /Class1,Div1
☐ Zone II /Class1,Div2

Other:
_____
_____
_____

Port Connections:

Thread Size
NPT _____
BSPP _____
SAE _____
Other _____

Flange Size
ANSI _____
DIN _____
Other _____

Constructions Materials:
☐ Brass ☐ Nickel Plated Brass ☐ Aluminum ☐ Galvanized Steel ☐ Nickel Plated Steel ☐ Stainless Steel
Other: _____

Electrical Connection: (select all that apply)
☐ DIN Connector ☐ Metal Terminal Box ☐ 1/2 Conduit Connector ☐ M12 X 1 (DESINA) ☐ Cable Gland
Other: _____

Options:
☐ Mounting Brackets ☐ Position Indicators → ☐ Open ☐ Close ☐ Both

Application Details:
Media: _____
Media Temperature Range: _____
Ambient Temperature Range: _____
Flow Rate: _____
Cv Required: _____
Maximum allowable Δ-P: _____
Switching Cycle: _____
Quantity: _____

Abrasive: YES ☐ NO ☐ Specific Gravity: _____
Pressure Range: _____
Reverse Pressure: _____
Vacuum: _____
Required Switching Time: _____

Need any of these Certifications: ☐ 3.1 Test Cert. ☐ CMTR ☐ Vacuum Test Other:

New Application: ☐ YES ☐ NO If NO, please explain why considering a change and define below.
Application Description: ☐ Price ☐ Performance ☐ Other

continue to page 2

Comments:

INSERT IMAGE HERE

1518 Grundy's Lane Bristol, PA 19007 | www.coaxvalves.com | info@coaxvalves.com | Phone: 215-757-3725 | Fax: 215-757-4060